

COMMERCIAL & LIGHT INDUSTRIAL TITANIUM IMMERSION HEATERS



Description

The HRZ range of titanium immersion heaters are designed for commercial and light industrial applications in hard water areas. The rotatable IP55 terminal box is provided for ease of wiring and flexible for access in all types of locations.

Key features

- For use in water applications only*
- Heavy duty titanium element – designed for hard water areas
- Flexible fitting and wiring options
- Flexible operational features (manual or fixed heat settings)
- IP55 rotatable enclosure
- Dual function thermostat
- Control Temp Maximum 80°C
- Safety Cut-Out 90°C

*Contact us for recommendations for chemical and oil applications



HRZ Light Industrial Titanium Immersion Heater

Technical specification

2 ¼" BSP	2" BSP	1 ¾" BSP	Loading (kW)	Voltage (V)	Phase Connection	Immersed Length (in/mm)	Watts Density (W/cm ²)
HRZ311A ISS 3	HRZ311B ISS 3	HRZ311C ISS 3	3	240/415	1/3 PH	11/280	7.7
HRZ316A ISS 3	HRZ316B ISS 3	HRZ316C ISS 3	3	240/415	1/3 PH	16/406	5.3
HRZ616A ISS 3	HRZ616B ISS 3	HRZ616C ISS 3	6	240/415	1/3 PH	16/406	9.6
HRZ624A ISS 3	HRZ624B ISS 3	HRZ624C ISS 3	6	240/415	1/3 PH	24/609	7
HRZ636A ISS 3	HRZ636B ISS 3	HRZ636C ISS 3	6	240/415	1/3 PH	36/914	4.8
HRZ916A ISS 3	HRZ916B ISS 3	HRZ916C ISS 3	9	240/415	1/3 PH	16/306	14.9
HRZ924A ISS 3	HRZ924B ISS 3	HRZ924C ISS 3	9	240/415	1/3 PH	24/609	10.5
HRZ936A ISS 3	HRZ936B ISS 3	HRZ936C ISS 3	9	240/415	1/3 PH	36/914	7.2
HRZ1224A ISS 3	HRZ1224B ISS 3	HRZ1224C ISS 3	12	415	3 PH	24/609	14.1
HRZ1236A ISS 3	HRZ1236B ISS 3	HRZ1236C ISS 3	12	415	3 PH	36/914	9.6

